TCP995 Console

Technical data sheet

Part Number: 107589





DESCRIPTION:

The TCP995 is ideal for panel mounted use in main or backup systems that require a reliable, easy and maintenance free solution. It can be used in combination with our TCS990 switch or as a standalone solution using IP connected ED137 radios and SIP telephony. The ergonomic and fast GUI is very flexible and can easily be tailored to your specific needs.
The product is designed with the latest techniques, such as capacitive touch. We have, however, ensured backward compatibility with our TCS990 series.

FEATURES:

- Capacitive touch screen
- Anti-glare

PARAMETER	SPECIFICATION
Connections	Dual redundant Ethernet E1 Support
Power	12V, max 2.92A (35W)
Dimensions	303 x 234 x 44mm (w x h x d) Weight 2.9 kg
Screen	Screen Resolution 1024 x 768 Screen size 12.1” Viewing angle -85°~85° (H&V) Brightness 1000 cd/m^2
Audio	Up to 4 individually driven speakers Up to 3 individual microphone inputs Up to 4 volume controls User-configurable audio routing and levels Console voice logging Last call functions
Applications	Main systems Backup systems ED137 compatible console
EMC	EN 55032, EN 55035
Operating Temperature	-20°C tot 50°C non-condensing (fanless)
Storage Temperature	-30°C tot 70°C

Although Jotron strives for accuracy in our datasheets, errors may occur. Please contact Jotron for the latest information as design and specifications may change without notice. Jotron is certified to NS-EN ISO 9001 / 14001 / 27001 and EASA has approved Jotron as a Design and Production Organization.