TDP995 (MIC) Console

Technical data sheet

Part Number: 107591



DESCRIPTION:

The TDP995 is a ideal for desktop use (it can be wall-mounted as well). The product is designed with the latest techniques, however we have ensured backward compatibility with our TCS990 series as well as forward compatibility with our future systems.

FEATURES:

- Resistive touch screen
- Configurable GRIDGUI interface
- Realtime clock with battery
- Footswitch connection

PARAMETER	SPECIFICATION
Connections	2 Ethernet connections E1 connection (with module)
Power	12V
Dimensions	350 x 190 x 80 mm
Touch Interface	Screen Resolution 800 x 480 Screen size 7” Viewing angle -85°~85° (H&V) Brightness 1300 cd/m^2
Audio	Internal loudspeaker Internal microphone or gooseneck microphone Integrated handset Headset connection 2 External loudspeaker connections External microphone connection 2 Internal volume controls 2 External connections for volume control Voice logging connection User-configurable audio routing and level control
Applications	Switchless Switch in combination with TCS990 ED137 compatible
EMC	EN55022, EN55024
Safety	EN60950
Temperature	-20°C tot 45°C (fanless)

Although Jotron strives for accuracy in our datasheets, errors may occur. Please contact Jotron for the latest information as design and specifications may change without notice. JOTRON is certified to NS-EN ISO 9001 / 14001 / 27001 and EASA has approved Jotron as a Design and Production Organization.