



TYPE APPROVAL CERTIFICATE

For a 406 Megahertz Distress Beacon for use with the Cospas-Sarsat Satellite System

Certificate Number: 375

Manufacturer: Jotron AS, Norway
Beacon Type(s): EPIRB Float Free
Beacon Models: Tron 60AIS
Test Laboratory: TÜV SÜD Product Service, United Kingdom
Date of Test: February – September 2021

Details of the beacon features and battery type are provided overleaf.

The Cospas-Sarsat Council hereby certifies that the 406 MHz Distress Beacon Model identified above is compatible with the Cospas-Sarsat System as defined in documents:

C/S T.001 Specification for Cospas-Sarsat 406 MHz Distress Beacon, Issue 4 – Revision 6, May 2020
C/S T.007 Cospas-Sarsat 406 MHz Distress Beacon Type Approval Standard, Issue 5 – Revision 5, May 2020

Original TAC 351 issued on: **6 January 2022**
RLS TAC 1351 issued on: **6 January 2022**
First extension TAC 375 issued on: **2 March 2023**

Steven W. Lett
Head of Cospas-Sarsat Secretariat

NOTE, HOWEVER:

1. This certificate does not authorize the operation or sale of any 406 MHz distress beacon. Such authorization may require type acceptance by national administrations in countries where the beacon will be distributed and may also be subject to national licensing requirements.
2. This certificate is intended only as a formal notification to the above identified manufacturer that the Cospas-Sarsat Council has determined, on the basis of test data of a beacon submitted by the manufacturer, that 406 MHz distress beacons of the type identified herein meet the standards for use with the Cospas-Sarsat System.
3. Although the manufacturer has formally stated that all beacons identified with the above model name(s) will meet the Cospas-Sarsat specification referenced above, this certificate is not a warranty and Cospas-Sarsat hereby expressly disclaims any and all liability arising out of or in connection with the issuance, use or misuse of the certificate.
4. This certificate is subject to revocation by the Cospas-Sarsat Council should the beacon type for which it is issued cease to meet the Cospas-Sarsat specification. A new certificate may be issued after satisfactory corrective action has been taken and correct performance demonstrated in accordance with the Cospas-Sarsat Type Approval Standard.
5. Cospas-Sarsat type approval testing requirements only address the electrical performance of the beacon at 406 MHz. Conformance of the beacon to operational and environmental requirements is the responsibility of national administrations.
6. This certificate authorizes the use of the registered name mark “Cospas-Sarsat” and of registered trademarks for the Programme’s logos, for labelling, instruction materials, and marketing of the 406-MHz beacon model identified, but not for other marketing or sales purposes (i.e., not for general uses beyond this specific beacon model).

| | |
|-------------------------------------|--|
| Beacon Models: | Tron 60AIS |
| Manufacturer: | Jotron AS, Norway |
| Operating temperature range: | -20°C to +55°C (Class 2) |
| Battery Details: | Lithium/Iron Disulfide (LiFeS ₂), Energizer, type L91, 8 x AA-size cells |
| Operating Lifetime: | 48 hours |
| Transmit Frequency: | 406.031 MHz |

Beacon Model Features:

- 121.5 MHz auxiliary radio locating device (power: 17 ±3 dBm, duty cycle: 50%)
- Strobe light (brightness: > 0.75 cd, duty cycle: 21 flashes/minute)
- Internal GPS receiver, manufacturer: Fastrax, model: uBlox, model MAX-M8Q, (GPS, Galileo, GLONASS)
- GNSS update rate: 5 minutes
- Format of operational messages: long
- Self-test mode, one burst of 520 ms
- GNSS self-test, one burst of 520 ms
- Integral antenna
- Automatic (via water contacts) and manual beacon activation
- Beacons were tested in EPIRB configuration (“floating in water”, “on deck” and “above ground”).

Approved Beacon Message Protocols: Beacon is approved for encoding with the message protocols indicated with "Yes" and black text below:

| USER PROTOCOLS | | USER-LOCATION PROTOCOLS | | LOCATION PROTOCOLS | |
|----------------|--|-------------------------|--|--------------------|--|
| No | Maritime with MMSI | No | Maritime with MMSI | Yes | Standard Location: EPIRB with MMSI |
| No | Maritime with Radio Call Sign | No | Maritime with Radio Call Sign | Yes | Standard Location: EPIRB with Serial Number |
| No | EPIRB Float Free with Serial Number | No | EPIRB Float Free with Serial Number | No | Standard Location: ELT with 24-bit Address |
| No | EPIRB Non Float Free with Serial Number | No | EPIRB Non Float Free with Serial Number | No | Standard Location: ELT with Aircraft Operator Designator |
| No | Radio Call Sign | No | Radio Call Sign | No | Standard Location: ELT with Serial Number |
| No | Aviation | No | Aviation | No | Standard Location: PLB with Serial Number |
| No | ELT with Serial Number | No | ELT with Serial Number | No | National Location: EPIRB |
| No | ELT with Aircraft Operator and Serial Number | No | ELT with Aircraft Operator and Serial Number | No | National Location: ELT |
| No | ELT with Aircraft 24-bit Address | No | ELT with Aircraft 24-bit Address | No | National Location: PLB |
| No | PLB with Serial Number | No | PLB with Serial Number | No | RLS Location: EPIRB |
| No | National (Short Format Message) | | | No | RLS Location: ELT |
| No | National (Long Format Message) | | | No | RLS Location: PLB |
| | | | | No | RLS Location: MMSI |
| | | | | No | ELT(DT) Location: ELT with Serial Number |
| | | | | No | ELT(DT) Location: ELT with Aircraft Operator and Serial Number |
| | | | | No | ELT(DT) Location: ELT with Aircraft 24-bit Address |